

Diesel Engine Fire Pump Controllers



Standard Features

- ViZiTouch operator interface
- NEMA 2 assembly
- Pressure and event recorder
- Battery voltage and amperage display
- Run Test push button
- HAND - OFF - AUTO selector switch
- Manual crank pushbuttons (2)
- Stop pushbutton
- Remote start / deluge valve start provision
- Pressure transducer and run test solenoid valve externally mounted
- Gland plate
- Audible alarm
- Alarm contacts for remote indication
- Weekly exercise programmable time clock
- Crank cycle
- Programmable automatic shutdown (minimum run timer)
- Programmable sequential start timer (delay start timer)



The Americas

**Tornatech Inc.
Head Office**
7075, Pl. Robert-Joncas
Suite # 132
Montreal, Canada
H4M 2Z2
Tel.: + 1 514 334 0523
+ 1 800 363 8448
Fax: + 1 514 334 5448

**USA Sales
Representative**
Tel.: + 1 513 307 6766
Fax: + 1 513 759 0509

**Latin America
Sales Representative**
Tel.: + 1 514 334 0523
Cell: + 1 514 945 4067
Fax: + 1 514 334 5448

Europe

Tornatech S.P.R.L.
Avenue Sabin 3
1300 Wavre
Belgium
Tel.: + 32 (0) 10 84 40 01
Fax: + 32 (0) 10 24 75 05

Middle East

Tornatech Fz-Llc.
P.O. Box 502221
Dubai, UAE
Tel.: + 971 50 8574639

Asia

Tornatech Pte Ltd.
49B Tuas South Ave 1
Tuas Cove
Industrial Centre
Singapore 637252
Tel.: + 65 6795 8114
+ 65 6795 7823
Fax: + 65 6795 3201

Shipping Weights and Dimensions

Model GPD - Diesel Engine Fire Pump Controller

	Wall Mount		
Starting Voltage	Approx shipping dimensions in inches (mm)	Approx shipping weight in Lbs (kg)	
12V.DC	32 L x 29 W x 16 H (813 x 737 x 407)	85 (39)	
24V.DC			